


TARA Wall-mounted basin mixer without pop-up waste - Dark Chrome

TARA

36 707 882



- 160mm projection
- fixed spout
- circular, air-enriched flow
- hole diameter valve 40 mm
- hole diameter spout 40 mm
- rosette Ø 55 mm
- max. flow 7 l/min
- lead-free
- WRAS
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

| | | |
|---|--------------------------------|---------------|
|  | Dark Chrome | 36 707 882-19 |
|  | Chrome | 36 707 882-00 |
|  | Brushed Platinum | 36 707 882-06 |
|  | Platinum | 36 707 882-08 |
|  | Brushed Durabronze (23kt Gold) | 36 707 882-28 |
|  | Matte Black | 36 707 882-33 |
|  | Brushed Dark Brass | 36 707 882-39 |
|  | Brushed Bronze | 36 707 882-42 |
|  | Brushed Champagne (22kt Gold) | 36 707 882-46 |
|  | Champagne (22kt Gold) | 36 707 882-47 |
|  | Brushed Chrome | 36 707 882-93 |
|  | Brushed Dark Platinum | 36 707 882-99 |

Required miscellaneous



- Concealed wall-mounted mixer centred spout -** 35 700 970 90
- max. recess depth 145 mm
 - min. recess depth 85 mm

Required miscellaneous



- Concealed wall-mounted mixer variable positioning -** 35 720 970 90
- min. recess depth 85 mm
 - max. recess depth 145 mm

36 707 882

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



TARA Wall-mounted basin mixer without pop-up waste - Dark Chrome

TARA

36 707 882

Certificates and sustainability

LGA_18

