








MADISON Rain shower with wall fixing 200 mm - Durabrand (23kt Gold)

28 545 977
Product version from 12/5/2019



- 435mm projection
- rain shower Ø 200 mm
- PURE RAIN, max. flow rate 14 l/min (at 3 bar)
- Function from: 8 l/min
- rosette Ø 55 mm
- 1/2" connection
- with anti-scale system

	Durabrand (23kt Gold)	28 545 977-09
	Chrome	28 545 977-00
	Brushed Platinum	28 545 977-06
	Platinum	28 545 977-08
	Brushed Durabrand (23kt Gold)	28 545 977-28
	Brushed Chrome	28 545 977-93
	Brushed Dark Platinum	28 545 977-99

Recommended miscellaneous




- Concealed wall elbow -

 - max. recess depth mm
 - min. recess depth mm

35 085 970 90

MADISON Rain shower with wall fixing 200 mm - Durabrand (23kt Gold)

28 545 977 Product version from 12/5/2019



Flow rate chart



Codes & Standards

DIN 4109	EN 1112	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		



MADISON Rain shower with wall fixing 200 mm - Durabrass (23kt Gold)

28 545 977 Product version from 12/5/2019

Certificates

DVGW_DW- 6517DN0	LGA_38	WRAS_250102
---------------------	--------	-------------

MADISON Rain shower with wall fixing 200 mm - Durabrand (23kt Gold)

28 545 977
Product version from 12/5/2019



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	09 27 35 003-09	rosette	1	40
2	90 14 10 026 00 90	seal	1	2
3	09 11 03 017-09	connection	1	40
4	04 12 05 038 01-09	shower	1	40