

**xTOOL Concealed thermostat without volume control 3/4" - Brushed Light Gold    SERIES SPECIFIC**

36 503 780    Product version from 9/1/2022



- cover plate 120 x 120 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

	Brushed Light Gold	36 503 780-27
	Chrome	36 503 780-00
	Brushed Platinum	36 503 780-06
	Platinum	36 503 780-08
	Dark Chrome	36 503 780-19
	Brushed Durabronze (23kt Gold)	36 503 780-28
	Matte Black	36 503 780-33
	Brushed Champagne (22kt Gold)	36 503 780-46
	Champagne (22kt Gold)	36 503 780-47
	Brushed Chrome	36 503 780-93
	Brushed Dark Platinum	36 503 780-99

**Required miscellaneous**

	<b>xTOOL Concealed thermostat module without volume control -</b>	35 503 970 90
	• min. recess depth 115 mm	
	• max. recess depth 155 mm	

**Recommended miscellaneous**

	<b>xGRID Attachment set for integrating in the dry wall construction -</b>	12 340 970 90
--	--	---------------

**Required miscellaneous**


	<b>xGRID Installation track 555 mm -</b>	12 360 970 90
--	--	---------------




xTOOL Concealed thermostat without volume control 3/4" - Brushed Light Gold    SERIES SPECIFIC

36 503 780    Product version from 9/1/2022

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		



xTOOL Concealed thermostat without volume control 3/4" - Brushed Light Gold    SERIES SPECIFIC

---

36 503 780    Product version from 9/1/2022

Certificates and sustainability

---

WRAS_2011	DVGW_DW- 6512DN0	LGA_29
-----------	---------------------	--------

**xTOOL Concealed thermostat without volume control 3/4" - Brushed Light Gold SERIES SPECIFIC**

36 503 780 Product version from 9/1/2022

