



xTOOL Concealed thermostat without volume control 3/4" - Champagne (22kt Gold)


IMO

36 503 985			
	<ul style="list-style-type: none"> cover plate 120 x 120 mm temperature control handle with safety limit stop at 38°C thermostat cartridge 	<div> <div></div> <div>Champagne (22kt Gold)</div> </div>	36 503 985-47
		<div> <div></div> <div>Chrome</div> </div>	36 503 985-00
		<div> <div></div> <div>Brushed Platinum</div> </div>	36 503 985-06
		<div> <div></div> <div>Platinum</div> </div>	36 503 985-08
		<div> <div></div> <div>Dark Chrome</div> </div>	36 503 985-19
		<div> <div></div> <div>Brushed Durabrass (23kt Gold)</div> </div>	36 503 985-28
		<div> <div></div> <div>Matte Black</div> </div>	36 503 985-33
		<div> <div></div> <div>Brushed Champagne (22kt Gold)</div> </div>	36 503 985-46
		<div> <div></div> <div>Brushed Chrome</div> </div>	36 503 985-93
		<div> <div></div> <div>Brushed Dark Platinum</div> </div>	36 503 985-99


Required miscellaneous

	xTOOL Concealed thermostat module without volume control - •max. recess depth 160 mm •min. recess depth 95 mm	35 503 970 90
---	--	---------------

Required miscellaneous

	xGRID Installation track 555 mm -	12 360 970 90
---	--	---------------

Recommended miscellaneous

	xGRID Attachment set for integrating in the dry wall construction -	12 340 970 90
---	--	---------------

xTOOL Concealed thermostat without volume control 3/4" - Champagne (22kt Gold)

IMO

36 503 985
mm [inches]



Flow rate chart



Certificates

WRAS_2011026. DVGW_DW- LGA_29930.
6512DN0706.

xTOOL Concealed thermostat without volume control 3/4" - Champagne (22kt Gold)

IMO

36 503 985

