






CYO Wall-mounted single-lever basin mixer without pop-up waste - Chrome

CYO

36 860 811



- 160mm projection
- fixed spout
- rectangular, air-enriched flow
- hole diameter spout 37 mm
- hole diameter single-lever mixer 57 mm
- rosette for mixer 80 x 80mm
- max. flow 4.5 l/min
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS

| | | |
|---|----------------------------------|---------------|
|  | Chrome | 36 860 811-00 |
|  | Brushed Platinum | 36 860 811-06 |
|  | Dark Chrome | 36 860 811-19 |
|  | Brushed Durabronz (23kt Gold) | 36 860 811-28 |
|  | Brushed Dark Platinum | 36 860 811-99 |

Required miscellaneous



Concealed wall-mounted single-lever mixer - 35 860 970 90

- max. recess depth 95 mm
- min. recess depth 80 mm
- mixer can be placed above, to the left or to the right of the spout.

36 860 811

mm [inches]



Flow rate chart



Codes & Standards

| | | | |
|-----------------------------|-----------|------------|--|
| ASME A112.18.1 | cUPC | DIN 4109 | EPA WaterSense |
| ISO 3822 | NSF372 | NSF61 | Scottish Water Byelaws |
| UK Water Supply Regulations | Ü-Zeichen | WaterSense |  |



CYO Wall-mounted single-lever basin mixer without pop-up waste - Chrome

CYO

36 860 811

Certificates and sustainability

IAPMO_N-4976

WRAS_2107

IAPMO_6397

LGA_38

IAPMO_8834

IAPMO_4976 (

36 860 811



Spare parts list

| No. | Item Number | Name | Quantity used | Delivery time |
|-----|--------------------|--|---------------|---------------|
| 9 | 90 15 05 064 01 90 | cartridge | 1.00 | 2 |
| 1 | 13 800 811-00 | CYO Wall-mounted basin spout without pop-up waste - Chrome | 1.00 | 10 |
| 7 | 09 27 78 039-00 | rosette | 1.00 | 10 |
| 2 | 09 24 03 072 10 90 | nipple | 1.00 | 2 |
| 3 | 09 20 80 021-00 | handle | 1.00 | 10 |
| 6 | 09 11 02 288-00 | cover | 1.00 | 10 |
| 5 | 90 31 20 087 00-00 | plug | 1.00 | 10 |
| 10 | 90 30 09 064 00 90 | key | 1.00 | 2 |
| 4 | 90 31 11 030 00 90 | pin | 1.00 | 2 |
| 8 | 90 14 10 049 00 90 | seal | 1.00 | 2 |