

SERENITY SKY Rain panel for recessed ceiling installation with light -Champagne (22kt Gold)

41 771 979



• expos	sea in	m pa	แเร
Rain	panel	with	2 (

- different spray modes
- PURIFY RAIN, 175 x 175 mm, max. flow rate 10 I/min (at 3 bar)
- FULL RAIN, 455 x 315 mm, max. flow rate 14 l/min (at 3 bar)
- Rain panel, 600 x 420 mm
- min. recess depth 150 mm
- weight 15kg
- feed pipe (hot/cold): 2x DN 20
- with anti-scale system
- Recommended control element: xTool

electrical:

- RGBW LED ambient lighting
- Electricity supply: 100-240 V AC, 50-60 Hz, 20 W
- system of protection: IP 65
- Feeder 3 x 1.5 mm2 NYM-J
- equipotential bonding 1 x 4mm2
- earth-leakage circuit-breaker 30 mA provided
- Provide DIN VDE 0100, Part 701 compliant safety
- Provided by customer: Zigbee gateway
- Not suitable for use in a steam room.

includes light bulbs with a Class G energy

includes light bulbs with a Class G energy efficiency

Required miscellaneous



SERENITY SKY Concealed ceiling 35 771 970 90


installation box with light -

- concealed rough parts •flush-mounted reflection box, 662 x
- 482 mm, RAL 9003, Signal White
- •2x female thread 1/2" connections
- •min. recess depth 150 mm
- •weight 15kg
- •Supply pipe 7 m
- •Input 100-240V AC 50-60Hz
- Output 24V DC SELV / Class II
- •ZigBee Light Link RGBW controller
- •Provided by customer: Zigbee gateway






SERENITY SKY Rain panel for recessed ceiling installation with light - Champagne (22kt Gold)



Flow rate chart





SERENITY SKY Rain panel for recessed ceiling installation with light - Champagne (22kt Gold)

41 771 979



SERENITY SKY Rain panel for recessed ceiling installation with light - Champagne (22kt Gold)

41 771 979

Spare parts list