















WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome

SERIES-VARIOUS


13 425 979




- 22mm projection
- PEARLSTREAM
- plate 240 mm x 60 mm
- connection 1/2", for shortening
- plug-link mounting
- Max. flow rate 9.5 l/min (at 3 bar)

	Dark Chrome	13 425 979-19
	Chrome	13 425 979-00
	Brushed Platinum	13 425 979-06
	Platinum	13 425 979-08
	Light Gold	13 425 979-26
	Brushed Light Gold	13 425 979-27
	Brushed Durabrass (23kt Gold)	13 425 979-28
	Matte Black	13 425 979-33
	Brushed Bronze	13 425 979-42
	Brushed Champagne (22kt Gold)	13 425 979-46
	Champagne (22kt Gold)	13 425 979-47
	Brushed Chrome	13 425 979-93
	Brushed Dark Platinum	13 425 979-99

Recommended miscellaneous

<div>  </div>	<div> Concealed wall elbow - <ul style="list-style-type: none"> • max. recess depth 163 mm • min. recess depth 90 mm </div>	35 085 970 90
--	--	---------------

Recommended miscellaneous

<div>  </div>	<div> Concealed wall elbow - <ul style="list-style-type: none"> • max. recess depth 163 mm • min. recess depth 90 mm </div>	35 085 970 90
--	--	---------------

WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome

SERIES-VARIOUS

13 425 979
mm [inches]



Flow rate chart



Trajectory diagram



Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Ü-Zeichen



WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome

SERIES-VARIOUS

13 425 979

Certificates and sustainability

LGA_19

IAPMO_4976

WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome

SERIES-VARIOUS

13 425 979

