

33 960 110



- 230mm projection
- pivotable spout 120°
- air-enriched flow and spray flow
- fabric braided hose 1500 mm
- max. flow 7 l/min at 3 bar flow pressure

Intrinsic protection against back flow.

33 960 110



Flow rate chart



Codes & Standards

DIN 4109

EN 1717

EN 817

ISO 3822

Ü-Zeichen

XP P 41-280



DORNBRACHT LYV Single-lever mixer Pull-out with spray function - Chrome


DORNBRACHT LYV

33 960 110

Certificates and sustainability

Belgaqua_23-012-2	AbP_10	ACS_23 ACC NY	DVGW_DW-6506DN0
-------------------	--------	---------------	-----------------

33 960 110



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
2	90 28 30 010 00-00	cover	1.00	2
4	90 18 40 227 00 90	insert	1.00	2
6	90 23 01 051 00 90	flow reducer	1.00	2
1	90 20 81 001 00-00	handle	1.00	2
8	90 12 11 181 00-00	shower	1.00	2
12	90 23 10 003 00 90	fixing set	1.00	2
9	90 14 15 062 00 90	gasket kit	1.00	2
13	04 30 04 100 00 90	hose	2.00	2
14	90 30 04 110 00 90	hose	1.00	2
5	90 30 02 101 00 90	hose	1.00	2
10	90 30 01 211 00 90	shaft	1.00	2
3	90 15 05 067 00 90	cartridge	1.00	2
7	90 14 05 081 00 90	seal	1.00	2
11	90 14 05 080 00 90	seal	1.00	2