







MADISON xTOOL Concealed thermostat without volume control 3/4" - Platinum
MADISON


36 503 977
Product version up to 1/1/2022



- cover plate Ø 124 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

	Platinum	36 503 977-08
	Chrome	36 503 977-00
	Brushed Platinum	36 503 977-06
	Durabrand (23kt Gold)	36 503 977-09
	Brushed Durabrand (23kt Gold)	36 503 977-28
	Brushed Dark Platinum	36 503 977-99


Required miscellaneous

	xTOOL Concealed thermostat module without volume control - •max. recess depth 110 mm •min. recess depth 85 mm	35 503 970 90
---	--	---------------


Required miscellaneous

	xGRID Installation track 555 mm -	12 360 970 90
---	--	---------------


Recommended miscellaneous

	xGRID Attachment set for integrating in the dry wall construction -	12 340 970 90
---	--	---------------

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		




MADISON xTOOL Concealed thermostat without volume control 3/4" - Platinum

MADISON

36 503 977 Product version up to 1/1/2022

Certificates and sustainability

WRAS_2011	DVGW_DW-6512DN0	LGA_29	LGA_29
-----------	-----------------	--------	--------



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
3	09 11 02 543-08	cover	1.00	40
2	90 11 01 196 00 90	base	1.00	2
4	09 31 11 048 90	pin	1.00	2
7	90 17 33 005 01-08	handle	1.00	40
6	90 21 02 112 00-08	sleeve	1.00	40
5	90 14 10 049 00 90	seal	1.00	2
1	90 15 02 063 00 90	cartridge	1.00	2