

SERENITY SKY Rain panel for recessed ceiling installation - Brushed Dark Platinum

41 770 979



- exposed trim parts
- Rain panel with 2 different spray modes
- PURIFY RAIN, 175 x 175 mm, max. flow rate 10 //min (at 3 bar)
 • FULL RAIN, 455 x 315 mm, max. flow rate 14 l/min
- (at 3 bar)
 Rain panel, 600 x 420 mm
- min. recess depth 150 mm
- weight 15kg
- feed pipe (hot/cold): 2x DN 20
- with anti-scale system
- Recommended control element: xTool
- Not suitable for use in a steam room.

	٩	Brushed Dark Platinum	41 770 979-99
1		Chrome	41 770 979-00
		Dark Chrome	41 770 979-19
	1	Brushed Bronze	41 770 979-42
		Brushed Champagne (22kt Gold)	41 770 979-46
		Champagne (22kt Gold)	41 770 979-47
		Brushed Stainless Steel	41 770 979-86

Required miscellaneous




SERENITY SKY Concealed ceiling 35 770 970 90 installation box -

- concealed rough parts
- •2x female thread 1/2" connections •flush-mounted reflection box, 662 x
- 482 mm, RAL 9003, Signal White
- •min. recess depth 150 mm
- weight 15kg
 Recommended control element:


xTool



SERENITY SKY Rain panel for recessed ceiling installation - Brushed Dark Platinum



Flow rate chart





SERENITY SKY Rain panel for recessed ceiling installation - Brushed Dark Platinum

41 770 979



SERENITY SKY Rain panel for recessed ceiling installation - Brushed Dark Platinum

41 770 979

Spare parts list