

SERENITY SKY Rain panel for recessed ceiling installation with light - Dark Chrome

exposed trim parts

41 771 979



- I I
 Rain panel with 2 different spray modes
PURIFY RAIN, 175 x 175 mm, max. flow rate 10 l/min (at 3 bar)
• FULL RAIN, 455 x 315 mm, max. flow rate 14 l/min (at 3 bar)
Rain panel, 600 x 420 mm
 min. recess depth 150 mm
weight 15kg
feed pipe (hot/cold): 2x DN 20
with anti-scale system
 Recommended control element: xTool

electrical:

- RGBW LED ambient lighting
- Electricity supply: 100-240 V AC, 50-60 Hz, 20 W
- system of protection: IP 65
- Feeder 3 x 1.5 mm2 NYM-J
- equipotential bonding 1 x 4mm2
- earth-leakage circuit-breaker 30 mA provided
- Provide DIN VDE 0100, Part 701 compliant safety
- zone 2
 Provided by customer: Zigbee gateway
- Not suitable for use in a steam room.

includes light bulbs with a Class G energy

includes light bulbs with a Class G energy efficiency

Required miscellaneous



SERENITY SKY Concealed ceiling 35 771 970 90 installation box with light -

- concealed rough parts
- •flush-mounted reflection box, 662 x
- 482 mm, RAL 9003, Signal White
- •2x female thread 1/2" connections
- •min. recess depth 150 mm
- •weight 15kg


- Supply pipe 7 m
 Input 100-240V AC 50-60Hz
 Output 24V DC SELV / Class II

 Output 24V DC SELV
- •ZigBee Light Link RGBW controller
- •Provided by customer: Zigbee gateway


	Dark Chrome	41 771 979-19
1	Chrome	41 771 979-00
	Brushed Bronze	41 771 979-42
	Brushed Champagne (22kt Gold)	41 771 979-46
	Champagne (22kt Gold)	41 771 979-47
	Brushed Stainless Steel	41 771 979-86
	Brushed Dark Platinum	41 771 979-99



SERENITY SKY Rain panel for recessed ceiling installation with light - Dark Chrome



Flow rate chart





SERENITY SKY Rain panel for recessed ceiling installation with light - Dark Chrome

41 771 979



SERENITY SKY Rain panel for recessed ceiling installation with light - Dark Chrome

41 771 979

Spare parts list