

ST 010 206 0980



- 220mm projection
- fixed spout
- circular, air-enriched flow
- hole diameter 37 mm
- rosette for spout 60 x 60mm
- 1/2" connection
- plug-link mounting
- max. flow 7 l/min
- lead-free
- automatic hygiene flush
- suitable for thermal disinfection
- adjustable follow-up time
- high-frequency sensors with self-calibration
- magnetic valve
- 100-240 V AC / 12 V DC, 50-60 Hz, 18 W power supply unit, incl. country-specific adapter set Cannot be combined with basins in conducting materials (e.g. steel. river stone). Cannot be combined with basins that have a closing drain.

 ATTENTION: Separate terms and conditions for electronic articles are applicable.

Individual components of this set

You need the following components for this set



Iv 42.76

42 766 970 90



1x 13 805 980-00



ST 010 206 0980



ST 010 206 0980



Fits: IMO, LULU, MADISON, MEM, TARA, CL.1, LISSÉ, VAIA, META, CYO

- automatic hygiene flush
- suitable for thermal disinfection
- adjustable follow-up time
- high-frequency sensors with self-calibration
- magnetic valve
- 100-240 V AC / 12 V DC, 50-60 Hz, 18 W power supply unit, incl. country-specific adapter set
 Cannot be combined with basins in conducting materials (e.g. steel. river stone).
 Cannot be combined with basins that have a closing drain.
 ATTENTION: Separate terms and conditions for

ATTENTION: Separate terms and conditions for electronic articles are applicable.

Cannot be combined with basins in conducting materials (e.g. steel. river stone).

Cannot be combined with basins that have a closing drain.

ATTENTION: Separate terms and conditions for electronic articles are applicable.

Required miscellaneous



eSET Touchfree Basin mixer without temperature setting for combining with free-standing fittings - 35 742 970 90

70.00



Required miscellaneous

eSET Touchfree Basin mixer without temperature setting for combining with wall-mounted fittings -

•min. recess depth 90 mm

•max. recess depth 125 mm


35 743 970 90


Recommended miscellaneous

Extension for Touchfree 500 mm - 1276597090



ST 010 206 0980 mm [inches]





Certificates


LGA_29120. WRAS_1906116. IAPMO_EGS. CE000001_eSet_Tou CE000002_eSet_Tou

chfree_20171206_D chfree_20171206_E E_signed. N_signed.

LGA_29119.



ST 010 206 0980



Spare parts list

Item Number	Name	Quantity used	Delivery time
90 10 01 177 00 90	electronic accessories	1	2
90 17 20 199 00 90	holder	1	2
04 30 50 079 00 90	valve	1	2
04 10 01 050 00 90	power supply	1	60
04 30 31 024 01 90	fixing set	1	2
	90 10 01 177 00 90 90 17 20 199 00 90 04 30 50 079 00 90 04 10 01 050 00 90	90 10 01 177 00 90 electronic accessories 90 17 20 199 00 90 holder 04 30 50 079 00 90 valve 04 10 01 050 00 90 power supply	90 10 01 177 00 90 electronic accessories 1 90 17 20 199 00 90 holder 1 04 30 50 079 00 90 valve 1 04 10 01 050 00 90 power supply 1



ST 010 206 0980




- 220mm projection
- fixed spout
- circular, air-enriched flow
- hole diameter 37 mm
- rosette 60 x 60 mm
- 1/2" connection
- plug-link mounting
- max. flow 7 l/min
- lead-free
- WRAS 1904065

For Touchfree control please order eSet Touchfree WITH or WITHOUT temperature adjustment

Recommended miscellaneous

Concealed wall elbow -

35 085 970 90









ST 010 206 0980



ST 010 206 0980 mm [inches]



Flow rate chart



Certificates

LGA_18593.

WRAS_1904065.



ST 010 206 0980

