

Concealed single-lever mixer with integrated shower connection - Brushed Platinum
SERIES-VARIOUS

36 050 970

Product version from 10/1/2023


Required miscellaneous

	<b>Concealed wall mounting -</b> ●max. recess depth 105 mm ●min. recess depth 80 mm	35 050 970 90
--	---	---------------


## Concealed single-lever mixer with integrated shower connection - Brushed Platinum

SERIES-VARIOUS

36 050 970 Product version from 10/1/2023  
mm [inches]



Flow rate chart



### Codes & Standards

DIN 4109

EN 1717

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen



## Concealed single-lever mixer with integrated shower connection - Brushed Platinum

SERIES-VARIOUS

---


36 050 970 Product version from 10/1/2023

Certificates and sustainability

---

Belgaqua\_21-025-2 WRAS\_2011

LGA\_29



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
2	09 24 04 266 90	nut	1.00	2
1	90 20 97 064 00-06	handle	1.00	10
12	09 18 40 230 90	connection	1.00	2
10	28 322 970-06	Metal shower hose 1/2" x 3/8" x 1750 mm - Brushed Platinum	1.00	2
13	09 14 10 061 90	seal	1.00	2
4	09 31 11 004 90	pin	1.00	60
6	09 14 10 213 90	seal	1.00	2
7	09 24 03 281-06	nipple	1.00	10
5	09 23 01 131 90	back-flow preventer	1.00	2
11	90 14 10 060 00 90	seal	1.00	2
8	90 21 02 069 00-06	cover	1.00	10
9	90 14 20 026 00 90	seal	1.00	2
3	90 15 05 044 04 90	cartridge	1.00	2