








## xTOOL Concealed thermostat without volume control 1/2" - Brushed Light Gold SERIES SPECIFIC

36 501 780 Product version from 9/1/2022



- cover plate 120 x 120 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

	Brushed Light Gold	36 501 780-27
	Chrome	36 501 780-00
	Brushed Platinum	36 501 780-06
	Platinum	36 501 780-08
	Dark Chrome	36 501 780-19
	Brushed Durabronze (23kt Gold)	36 501 780-28
	Matte Black	36 501 780-33
	Brushed Chrome	36 501 780-93
	Brushed Dark Platinum	36 501 780-99

### Required miscellaneous




- xTOOL Concealed thermostat module without volume control -** 35 503 970 90
- min. recess depth 115 mm
  - max. recess depth 155 mm


**xTOOL Concealed thermostat without volume control 1/2" - Brushed Light Gold**    **SERIES SPECIFIC**

36 501 780    Product version from 9/1/2022

mm [inches]



**Flow rate chart**



**Codes & Standards**

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		



xTOOL Concealed thermostat without volume control 1/2" - Brushed Light Gold    SERIES SPECIFIC

---

36 501 780    Product version from 9/1/2022

Certificates and sustainability

---

WRAS_2011	DVGW_DW- 6512DN0	LGA_29
-----------	---------------------	--------

**xTOOL Concealed thermostat without volume control 1/2" - Brushed Light Gold SERIES SPECIFIC**

36 501 780 Product version from 9/1/2022

