

17 861 790 Product version from 3/9/2016 to 5/27/2021



- 142mm projection
- rigid, thermally insulated spout
- laminar flow
- height of mixer 248 mm
- height up to laminar flow regulator 226 mm
- hole diameter 35 mm
- provides filtered, hot water up to 93°C
- provides filtered, cold water
- max. flow 2 l/min at 3 bar flow pressure
- ready-to-use control unit for wall mounting (137mm x 159mm x 60mm)
- electronic magnetic valve
- 100-230 V, 50-60 Hz, 18 W power supply unit, incl. country-specific adapter set
- lead-free
- Spout ring cannot be removed.
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.

The installation must be above a kitchen sink.

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at

www.dornbracht.com/professional Not compatible with reverse osmosis filtration

A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.

The installation must be above a kitchen sink.

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at www.dornbracht.com/professional

Not compatible with reverse osmosis filtration

Chrome	17 861 790-00
Brushed Platinum	17 861 790-06
Platinum	17 861 790-08
Dark Chrome	17 861 790-19
Brushed Durabrass (23kt Gold)	17 861 790-28
Brushed Champagne (22kt Gold)	17 861 790-46
Champagne (22kt Gold)	17 861 790-47
Brushed Chrome	17 861 790-93
Brushed Dark Platinum	17 861 790-99

#### Required miscellaneous




Hot water tank incl. filter -


12 892 970 90



#### 17 861 790 Product version from 3/9/2016 to 5/27/2021



### Flow rate chart



### Codes & Standards

NSF372

ASME A112.18.1	cUPC	DIN 4109	ISO 3822

Ü-Zeichen

NSF61



ELIO

17 861 790 Product version from 3/9/2016 to 5/27/2021

Certificates and sustainability

IAPMO\_N-4


IAPMO\_4976

LGA\_28

IAPMO\_6



17 861 790 Product version from 3/9/2016 to 5/27/2021



# Spare parts list

No.		Item Number	Name	Quantity used	Delivery time
	4	04 10 01 246 00 90	electronic accessories	1.00	2
	9	09 16 01 045 90	ring	1.00	2
	7	90 24 04 291 00 90	insert	1.00	2
	3	90 10 01 048 00 90	electronic accessories	1.00	2
	2	90 30 04 067 00 90	hose	1.00	2
	8	09 24 04 293 90	nipple	1.00	2
	5	12 866 970 90	Adapter Flow restrictor HCWD 3/8" -	1.00	2
	1	90 17 85 100 04-00	fitting	1.00	10
	6	90 11 11 064 01 90	electronic accessories	1.00	2