

## Bidet spray - Brushed Durabronze (23kt Gold)

SERIES-VARIOUS







27 701 970 Product version from 10/1/2023



- wall bracket with integrated safety shut off valve
- max. standing pressure: 5bar
- hand shower with back flow preventer
- 1/2" shower outlet
- rosette Ø 60 mm
- metal shower hose 1250mm with integrated anti-twist protection

This product does not provide intrinsic protection against backflow in accordance with DIN EN 1717. This product must not be installed and operated in countries where compliance with DIN EN 1717 is stipulated.

The bidet shower must be operated with an upstream main fitting.

	Brushed Durabronze (23kt Gold)	27 701 970-28
	Chrome	27 701 970-00
	Brushed Platinum	27 701 970-06
	Platinum	27 701 970-08
	Durabronze (23kt Gold)	27 701 970-09
	Dark Chrome	27 701 970-19
	Light Gold	27 701 970-26
	Brushed Light Gold	27 701 970-27
	Brushed Dark Brass	27 701 970-39
	Brushed Bronze	27 701 970-42
	Brushed Champagne (22kt Gold)	27 701 970-46
	Champagne (22kt Gold)	27 701 970-47
	Brushed Chrome	27 701 970-93
	Brushed Dark Platinum	27 701 970-99

### Recommended miscellaneous



#### Concealed wall elbow -

35 085 970 90

- max. recess depth 163 mm
- min. recess depth 90 mm

mm [inches]



**Flow rate chart**



**Codes & Standards**

DIN 4109                      ISO 3822                      Ü-Zeichen



## Bidet spray - Brushed Durabrass (23kt Gold)

SERIES-VARIOUS

27 701 970 Product version from 10/1/2023

Certificates and sustainability

LGA\_29



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	4 09 23 01 097 90	back-flow preventer	1.00	2
	2 12 861 970-28	accessories	1.00	-
Spare part can no longer be ordered, please order the replacement item				
	1 09 30 09 029 90	key	1.00	2
	6 90 30 02 001 00-28	hose	1.00	20
	5 90 11 03 001 00-28	connection	1.00	20
	3 90 12 11 107 00-28	shower	1.00	20