

Wall elbow - Dark Chrome

SERIES SPECIFIC

28 450 625



- 3/8" shower outlet
- rosette Ø 55 mm
- 1/2" connection
- WRAS

Intrinsic protection against back flow.

	Dark Chrome	28 450 625-19
	Chrome	28 450 625-00
	brushed chrome	28 450 625-04
	Brushed Platinum	28 450 625-06
	Platinum	28 450 625-08
	Light Gold	28 450 625-26
	Brushed Light Gold	28 450 625-27
	Brushed Durabronze (23kt Gold)	28 450 625-28
	Matte Black	28 450 625-33
	Brushed Dark Brass	28 450 625-39
	Brushed Bronze	28 450 625-42
	aluminium	28 450 625-45
	Brushed Champagne (22kt Gold)	28 450 625-46
	Champagne (22kt Gold)	28 450 625-47
	Brushed Chrome	28 450 625-93
	Brushed Dark Platinum	28 450 625-99

Recommended miscellaneous




- Concealed wall elbow -**
- max. recess depth 163 mm
 - min. recess depth 90 mm


35 085 970 90

28 450 625

mm [inches]



Flow rate chart



Codes & Standards

ASME A112.18.1	cUPC	EN 1717	Scottish Water Byelaws
----------------	------	---------	---------------------------

UK Water Supply
Regulations



Wall elbow - Dark Chrome

SERIES SPECIFIC

28 450 625

Certificates and sustainability

Belgaqua_21-381-2 IAPMO_4976 WRAS_240702

28 450 625

