



WATER FALL Cascade spout with individual jets for wall mounting - Matte Black

SERIES-VARIOUS

13 425 979	Product version from 10/1/2023		
	<ul style="list-style-type: none"> • 22mm projection • PEARLSTREAM • plate 240 mm x 60 mm • connection 1/2", for shortening • plug-link mounting • Max. flow rate 9.5 l/min (at 3 bar) 		
			
		<div> <div></div> <div>Matte Black</div> <div>13 425 979-33</div> </div>	
		<div> <div></div> <div>Chrome</div> <div>13 425 979-00</div> </div>	
		<div> <div></div> <div>Brushed Platinum</div> <div>13 425 979-06</div> </div>	
		<div> <div></div> <div>Platinum</div> <div>13 425 979-08</div> </div>	
		<div> <div></div> <div>Dark Chrome</div> <div>13 425 979-19</div> </div>	
		<div> <div></div> <div>Light Gold</div> <div>13 425 979-26</div> </div>	
		<div> <div></div> <div>Brushed Light Gold</div> <div>13 425 979-27</div> </div>	
		<div> <div></div> <div>Brushed Durabrass (23kt Gold)</div> <div>13 425 979-28</div> </div>	
		<div> <div></div> <div>Brushed Bronze</div> <div>13 425 979-42</div> </div>	
		<div> <div></div> <div>Brushed Champagne (22kt Gold)</div> <div>13 425 979-46</div> </div>	
		<div> <div></div> <div>Champagne (22kt Gold)</div> <div>13 425 979-47</div> </div>	
		<div> <div></div> <div>Brushed Chrome</div> <div>13 425 979-93</div> </div>	
		<div> <div></div> <div>Brushed Dark Platinum</div> <div>13 425 979-99</div> </div>	

Recommended miscellaneous




Concealed wall elbow -

- max. recess depth 163 mm
- min. recess depth 90 mm

35 085 970 90

Recommended miscellaneous



Concealed wall elbow -

- max. recess depth 163 mm
- min. recess depth 90 mm

35 085 970 90

WATER FALL Cascade spout with individual jets for wall mounting - Matte Black

SERIES-VARIOUS

13 425 979 Product version from 10/1/2023
mm [inches]



Flow rate chart



Trajectory diagram



Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Ü-Zeichen



WATER FALL Cascade spout with individual jets for wall mounting - Matte Black

SERIES-VARIOUS

13 425 979 Product version from 10/1/2023

Certificates and sustainability

LGA_19

IAPMO_4976



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
4	90 24 03 199 00 90	connection	1.00	2
5	90 31 20 087 00-33	plug	1.00	30
6	09 31 11 144 90	pin	2.00	2
1	04 30 31 024 01 90	fixing set	1.00	2
2	09 14 05 009 90	seal	1.00	2
7	09 17 01 185 20-33	spout	1.00	30
3	09 17 97 053 90	holder	1.00	2
8	90 29 03 071 00 90	insert	1.00	2