



- 146mm projection
- rigid, thermally insulated spout
- laminar flow
- height of mixer 288 mm
- height up to laminar flow regulator 180 mm
- hole diameter 35 mm
- provides filtered, hot water up to 93°C
- provides filtered, cold water
- max. flow 2 l/min at 3 bar flow pressure
- ready-to-use control unit for wall mounting (137mm x 159mm x 60mm)
- electronic magnetic valve
- 100-230 V, 50-60 Hz, 18 W power supply unit, incl. country-specific adapter set
- lead-free
- Spout ring cannot be removed.
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.

The installation must be above a kitchen sink.

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at [www.dornbracht.com/professional](http://www.dornbracht.com/professional)

Not compatible with reverse osmosis filtration

|   |                               |               |
|---|-------------------------------|---------------|
|    | Brushed Chrome                | 17 861 875-93 |
|    | Chrome                        | 17 861 875-00 |
|    | Brushed Platinum              | 17 861 875-06 |
|    | Platinum                      | 17 861 875-08 |
|    | Durabrand (23kt Gold)         | 17 861 875-09 |
|    | Dark Chrome                   | 17 861 875-19 |
|    | Brushed Durabrand (23kt Gold) | 17 861 875-28 |
|    | Matte Black                   | 17 861 875-33 |
|    | Brushed Champagne (22kt Gold) | 17 861 875-46 |
|   | Champagne (22kt Gold)         | 17 861 875-47 |
|  | Brushed Dark Platinum         | 17 861 875-99 |

17 861 875 Product version from 5/28/2022



**Flow rate chart**



**Codes & Standards**

ASME A112.18.1

cUPC

Executive Order  
no. 1007

NSF372

NSF61



TARA ULTRA HOT & COLD WATER DISPENSER - Brushed Chrome

TARA ULTRA

17 861 875    Product version from 5/28/2022

Certificates and sustainability

|           |          |         |              |
|-----------|----------|---------|--------------|
| IAPMO_N-4 | GDV_0400 | IAPMO_6 | IAPMO_4976 ( |
|-----------|----------|---------|--------------|

17 861 875 Product version from 5/28/2022

Parts for other  
finishes can be found  
here: [Chrome](#)

