








TARA ULTRA Profi single-lever mixer - Brushed Bronze
TARA ULTRA


33 860 875
Product version from 5/2/2022



- 240mm projection
 - pivotable 360°
 - air-enriched flow and spray flow
 - height of mixer 685 mm
 - height up to aerator 129 mm
 - hole diameter 35 mm
 - sprayface with anti-scaling system
 - max. flow 8 l/min at 3 bar flow pressure
 - lead-free
 - This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- Intrinsic protection against back flow.

	Brushed Bronze	33 860 875-42
	Chrome	33 860 875-00
	Brushed Platinum	33 860 875-06
	Platinum	33 860 875-08
	Dark Chrome	33 860 875-19
	Brushed Chrome	33 860 875-93
	Brushed Dark Platinum	33 860 875-99

Recommended miscellaneous



Strainer waste with control handle
10 712 970-42

- Brushed Bronze

Recommended miscellaneous



Dispenser without rosette -
82 424 970-42

Brushed Bronze



Flow rate chart



Codes & Standards

DIN 4109

EN 1717

ISO 3822

Ü-Zeichen



TARA ULTRA Profi single-lever mixer - Brushed Bronze

TARA ULTRA

33 860 875 Product version from 5/2/2022

Certificates and sustainability

LGA_18

Belgaqua_22_277_2

33 860 875 Product version from 5/2/2022

Parts for other
finishes can be found
here: [Chrome](#)

