

LISSÉ Hand shower set with individual rosettes - Brushed Chrome

LISSÉ

27 802 845 Product version from 3/9/2016 to 6/3/2020



- COMPACT RAIN, max. flow rate 15 l/min (at 3 bar)
- with anti-scale system
- 3/8" shower outlet










Technical data:

- rosette for wall elbow 60 x 78mm
- rosette for shower holder 60 x 78mm
- metal shower hose 1250mm with integrated anti-twist protection
- 1/2" wall elbow

Notes:

- WRAS

Intrinsic protection against back flow.

	Brushed Chrome	27 802 845-93
	Chrome	27 802 845-00
	Chrome	27 802 845-00 0010
	Brushed Platinum	27 802 845-06
	Brushed Platinum	27 802 845-06 0010
	Dark Chrome	27 802 845-19
	Dark Chrome	27 802 845-19 0010
	Brushed Light Gold	27 802 845-27
	Brushed Light Gold	27 802 845-27 0010
	Matte Black	27 802 845-33
	Matte Black	27 802 845-33 0010
	Brushed Chrome	27 802 845-93 0010
	Brushed Dark Platinum	27 802 845-99
	Brushed Dark Platinum	27 802 845-99 0010

Recommended miscellaneous

Concealed wall elbow -


35 085 970 90



- min. recess depth 90 mm
- max. recess depth 163 mm

27 802 845 Product version from 3/9/2016 to 6/3/2020

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen




LISSE Hand shower set with individual rosettes - Brushed Chrome

LISSE

27 802 845 Product version from 3/9/2016 to 6/3/2020

Certificates and sustainability

LGA_29	LGA_29	WRAS_2209
--------	--------	-----------



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	28 450 845-93	LISSÉ Wall elbow - Brushed Chrome	1.00	10
5	28 019 979-93	Hand shower - Brushed Chrome	1.00	-
Spare part can no longer be ordered, please order the replacement item				
4	90 30 02 072 00-93	Metal shower hose 1/2" x 3/8" x 1250 mm - Brushed Chrome	1.00	20
3	28 050 845-93	LISSÉ Wall bracket - Brushed Chrome	1.00	20
2	90 14 20 026 00 90	seal	1.00	2