















WATER FALL Cascade spout with individual jets for wall mounting - Brushed Light Gold

SERIES-VARIOUS

13 425 979	Product version from 10/1/2023		
	<ul style="list-style-type: none"> PEARLSTREAM Max. flow rate 9.5 l/min (at 3 bar) Function from: l/min 		
	Technical data: <ul style="list-style-type: none"> plate 240 mm x 60 mm 22mm projection connection 1/2", for shortening plug-link mounting 		
			Brushed Light Gold 13 425 979-27
			Chrome 13 425 979-00
			Brushed Platinum 13 425 979-06
			Platinum 13 425 979-08
			Dark Chrome 13 425 979-19
			Light Gold 13 425 979-26
			Brushed Durabronze (23kt Gold) 13 425 979-28
			Matte Black 13 425 979-33
			Brushed Dark Brass 13 425 979-39
			Brushed Bronze 13 425 979-42
			Brushed Champagne (22kt Gold) 13 425 979-46
			Champagne (22kt Gold) 13 425 979-47
			Brushed Chrome 13 425 979-93
			Brushed Dark Platinum 13 425 979-99

Recommended miscellaneous

	Concealed wall elbow - <ul style="list-style-type: none"> min. recess depth 90 mm max. recess depth 163 mm 	35 085 970 90
--	--	---------------


Recommended miscellaneous

	Concealed wall elbow - <ul style="list-style-type: none"> min. recess depth 90 mm max. recess depth 163 mm 	35 085 970 90
--	--	---------------

WATER FALL Cascade spout with individual jets for wall mounting - Brushed Light Gold

SERIES-VARIOUS

13 425 979 Product version from 10/1/2023
mm [inches]



Flow rate chart



Trajectory diagram



Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



WATER FALL Cascade spout with individual jets for wall mounting - Brushed Light Gold SERIES-VARIOUS

13 425 979 Product version from 10/1/2023

Certificates and sustainability

LGA_19



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	3 09 17 97 053 90	holder	1.00	2
	5 90 31 20 087 00-27	plug	1.00	30
	8 90 29 03 071 00 90	insert	1.00	2
	6 09 31 11 144 90	pin	2.00	2
	4 90 24 03 199 00 90	connection	1.00	2
	1 04 30 31 024 01 90	fixing set	1.00	2
	7 09 17 01 185 20-27	spout	1.00	60
	2 09 14 05 009 90	seal	1.00	2