

**WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome**

13 425 979



- 22mm projection
- PEARLSTREAM
- plate 240 mm x 60 mm
- connection 1/2", for shortening
- plug-link mounting
- Max. flow rate 9.5 l/min (at 3 bar)

	Dark Chrome	13 425 979-19
	Chrome	13 425 979-00
	Brushed Platinum	13 425 979-06
	Platinum	13 425 979-08
	Light Gold	13 425 979-26
	Brushed Light Gold	13 425 979-27
	Brushed Durabronze (23kt Gold)	13 425 979-28
	Matte Black	13 425 979-33
	Brushed Bronze	13 425 979-42
	Brushed Champagne (22kt Gold)	13 425 979-46
	Champagne (22kt Gold)	13 425 979-47
	Brushed Chrome	13 425 979-93
	Brushed Dark Platinum	13 425 979-99

**Recommended miscellaneous**



- Concealed wall elbow -**
- min. recess depth mm
  - max. recess depth mm

35 085 970 90

**Recommended miscellaneous**




- Concealed wall elbow -**
- min. recess depth mm
  - max. recess depth mm

35 085 970 90




# WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome


13 425 979  
mm [inches]



Flow rate chart



Trajectory diagram



## Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

## Ü-Zeichen



## WATER FALL Cascade spout with individual jets for wall mounting - Dark Chrome

---

13 425 979

Certificates

---

LGA\_19

IAPMO\_4976

WATER FALL Cascade spout with individual jets for wall mounting - Dark  
Chrome

---

13 425 979

