

17 861 680



- 145mm projection
- rigid, thermally insulated spout
- laminar flow
- height of mixer 233 mm
- height up to laminar flow regulator 213 mm
- hole diameter 35 mm
- provides filtered, hot water up to 93°C
- provides filtered, cold water
- max. flow 2 l/min at 3 bar flow pressure
- ready-to-use control unit for wall mounting (137mm x 159mm x 60mm)
- electronic magnetic valve
- 100-230 V, 50-60 Hz, 18 W power supply unit, incl. country-specific adapter set
- lead-free
- Spout ring cannot be removed.
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and filter.

In addition, the installation must be above a kitchen sink.

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at www.dornbracht.com/professional

A minimum flow pressure of 3 bar is necessary for the HOT & COLD WATER DISPENSER to work perfectly in conjunction with a hot water tank and

In addition, the installation must be above a kitchen sink.

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at www.dornbracht.com/professional

		Chrome	17 861	680-00
		Brushed Platinum	17 861	680-06
		Platinum	17 861	680-08
	r	Dark Chrome	17 861	680-19
		Brushed Durabrass (23kt Gold)	17 861	680-28
		Brushed Champagne (22kt Gold)	17 861	680-46
		Champagne (22kt Gold)	17 861	680-47
	٩	Brushed Dark Platinum	17 861	680-99

#### Required miscellaneous




Hot water tank incl. filter -


12 892 970 90



#### 17 861 680



### Flow rate chart



### Codes & Standards

ASME A112.18.1	cUPC	DIN 4109	ISO 3822	

NSF372 NSF61 Ü-Zeichen



LOT

17 861 680

Certificates

IAPMO\_4976

IAPMO\_N-4

LGA\_28


IAPMO\_6



17 861 680

Product version from 4/1/2014 to 5/27/2021 Product version from 5/27/2021 to 5/28/2022

### **Product version from 5/28/2022**





17 861 680

# Spare parts list

Product version from 4/1/2014 to 5/27/2021

Product version from 5/27/2021 to 5/28/2022

### **Product version from 5/28/2022**

No.	Item Number	Name	Quantity used	Delivery time
	90 17 85 100 03-00	fitting	9	10