

## WATER FALL Cascade spout for wall mounting - Dark Chrome

13 420 979



- 120mm projection
- CASCADE, max. flow rate 26.5 l/min (at 3 bar)
- cover plate 240 x 60 mm
- 1/2" connection
- plug-link mounting
- WRAS

	Dark Chrome	13 420 979-19
	Chrome	13 420 979-00
	Brushed Platinum	13 420 979-06
	Platinum	13 420 979-08
	Light Gold	13 420 979-26
	Brushed Light Gold	13 420 979-27
	Brushed Durabronze (23kt Gold)	13 420 979-28
	Matte Black	13 420 979-33
	Brushed Bronze	13 420 979-42
	Brushed Champagne (22kt Gold)	13 420 979-46
	Champagne (22kt Gold)	13 420 979-47
	Brushed Chrome	13 420 979-93

### Recommended miscellaneous



- Concealed wall elbow -**
- max. recess depth mm
  - min. recess depth mm

35 085 970 90

### Recommended miscellaneous




- Concealed wall elbow -**
- max. recess depth mm
  - min. recess depth mm

35 085 970 90


## WATER FALL Cascade spout for wall mounting - Dark Chrome

13 420 979


mm [inches]



Flow rate chart



Trajectory diagram



### Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

### Ü-Zeichen



## WATER FALL Cascade spout for wall mounting - Dark Chrome

---

13 420 979

### Certificates

---

LGA\_18

IAPMO\_4976

## WATER FALL Cascade spout for wall mounting - Dark Chrome

13 420 979

