

















WATER FALL Cascade spout with individual jets for wall mounting - Brushed Light Gold

13 425 979	Product version from 10/1/2023		
	<ul style="list-style-type: none"> • 22mm projection • PEARLSTREAM • plate 240 mm x 60 mm • connection 1/2", for shortening • plug-link mounting • Max. flow rate 9.5 l/min (at 3 bar) 		
			Brushed Light Gold 13 425 979-27
			Chrome 13 425 979-00
			Brushed Platinum 13 425 979-06
			Platinum 13 425 979-08
			Dark Chrome 13 425 979-19
			Light Gold 13 425 979-26
			Brushed Durabrass (23kt Gold) 13 425 979-28
			Matte Black 13 425 979-33
			Brushed Bronze 13 425 979-42
			Brushed Champagne (22kt Gold) 13 425 979-46
			Champagne (22kt Gold) 13 425 979-47
			Brushed Chrome 13 425 979-93
			Brushed Dark Platinum 13 425 979-99

Recommended miscellaneous


	Concealed wall elbow -	35 085 970 90
	<ul style="list-style-type: none"> • min. recess depth mm • max. recess depth mm 	

Recommended miscellaneous


	Concealed wall elbow -	35 085 970 90
	<ul style="list-style-type: none"> • min. recess depth mm • max. recess depth mm 	

WATER FALL Cascade spout with individual jets for wall mounting - Brushed Light Gold


13 425 979 Product version from 10/1/2023
mm [inches]



Flow rate chart



Trajectory diagram



Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



WATER FALL Cascade spout with individual jets for wall mounting - Brushed Light Gold


13 425 979 Product version from 10/1/2023

Certificates

LGA_19

WATER FALL Cascade spout with individual jets for wall mounting - Brushed Light Gold

13 425 979 Product version from 10/1/2023



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	04 30 31 024 01 90	fixing set	1	2
2	09 14 05 009 90	seal	1	2
3	09 17 97 053 90	holder	1	2
4	90 24 03 199 00 90	connection	1	2
5	90 31 20 087 00-27	plug	1	30
6	09 31 11 144 90	pin	2	2
7	09 17 01 185 20-27	spout	1	60
8	90 29 03 071 00 90	insert	1	2