








IMO Bath spout for wall mounting - Chrome

13 801 670    Product version from 4/1/2024



- 200mm projection
- rectangular normal flow
- hole diameter 37 mm
- 1/2" connection
- max. flow 25.1 l/min at 3 bar flow pressure
- WRAS

	Chrome	13 801 670-00
	Brushed Platinum	13 801 670-06
	Dark Chrome	13 801 670-19
	Brushed Light Gold	13 801 670-27
	Matte Black	13 801 670-33
	Brushed Chrome	13 801 670-93
	Brushed Dark Platinum	13 801 670-99

Recommended miscellaneous



- Concealed wall elbow -

•max. recess depth mm


•min. recess depth mm

35 085 970 90


# IMO Bath spout for wall mounting - Chrome

13 801 670    Product version from 4/1/2024

mm [inches]



Flow rate chart



## Codes & Standards

ASME A112.18.1	cUPC	Scottish Water Byelaws	UK Water Supply Regulations
----------------	------	------------------------	-----------------------------



## IMO Bath spout for wall mounting - Chrome

---

13 801 670 Product version from 4/1/2024

### Certificates


---

IAPMO\_4976

WRAS\_2005

# IMO Bath spout for wall mounting - Chrome

13 801 670    Product version from 4/1/2024



## Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	09 18 40 139 90	base	1	2
2	09 27 67 008-00	rosette	1	10
3	09 23 01 057 90	flow reducer	1	2
4	04 28 22 241 00-00	spout	1	10