

TARA ULTRA BAR TAP Single-lever mixer - Brushed Champagne (22kt Gold)

TARA ULTRA

33 805 875



- 166mm projection
- gauge mm
- pivotable spout 360°
- laminar flow
- height of mixer 303 mm
- height up to laminar flow regulator 186 mm
- hole diameter 35 mm
- max. flow 8 l/min at 3 bar flow pressure
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Brushed Champagne (22kt Gold)	33 805 875-46
	Chrome	33 805 875-00
	Brushed Platinum	33 805 875-06
	Platinum	33 805 875-08
	Durabrass (23kt Gold)	33 805 875-09
	Dark Chrome	33 805 875-19
	Brushed Durabrass (23kt Gold)	33 805 875-28
	Matte Black	33 805 875-33
	Brushed Bronze	33 805 875-42
	Champagne (22kt Gold)	33 805 875-47
	Brushed Chrome	33 805 875-93
	Brushed Dark Platinum	33 805 875-99

Recommended miscellaneous


**Dispenser without rosette -
Brushed Champagne (22kt Gold)** 82 424 970-46




Recommended miscellaneous

**Strainer waste with control handle
- Brushed Champagne (22kt Gold)** 10 712 970-46





Technical drawing showing two views of the G3/8 component. The left view is a side elevation showing dimensions: overall height 198 [7 7/8"], top flange width 166 [6 1/2"], base diameter Ø 46 [1 3/4"], mounting hole diameter Ø 35 [1 3/8"], and a maximum length of 72 [2 7/8"] for the threaded section. A detail callout shows a cross-section of the mounting hole with a depth of 40 [1 5/8"]. The right view is a front elevation showing a U-shaped profile with a total width of 198 [7 7/8"], a central opening width of 166 [6 1/2"], and a height of 186 [7 1/4"] from the base to the top of the arch. An angle of 18 [1 1/2°] is indicated at the base of the arch. Both views show a base thread of G 3/8."/>





TARA ULTRA BAR TAP Single-lever mixer - Brushed Champagne (22kt Gold)

TARA ULTRA

33 805 875

Certificates and sustainability

LGA_18

33 805 875

Parts for other
finishes can be found
here: [Chrome](#)

