

## WATER POINTS Concealed body spray FlowReduce - Light Gold

36 515 979



- HORIZONTAL RAIN, max. flow rate 6 l/min (at 3 bar)
- with anti-scale system
- cover plate 120 x 120 mm
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS

**Flow restrictor (8.3 l/min) to extend shower jet from approx. 500 mm to approx. 1000 mm**

Flow restrictor (8.3 l/min) to extend shower jet from approx. 500 mm to approx. 1000 mm

	Light Gold	36 515 979-26
	Chrome	36 515 979-00
	Brushed Platinum	36 515 979-06
	Platinum	36 515 979-08
	Dark Chrome	36 515 979-19
	Brushed Light Gold	36 515 979-27
	Brushed Durabronze (23kt Gold)	36 515 979-28
	Matte Black	36 515 979-33
	Brushed Bronze	36 515 979-42
	Brushed Champagne (22kt Gold)	36 515 979-46
	Champagne (22kt Gold)	36 515 979-47
	Brushed Chrome	36 515 979-93
	Brushed Dark Platinum	36 515 979-99

### Required miscellaneous



**WATER POINTS Adapter plate -** 12 305 970 90

### Required miscellaneous



**Concealed wall installation box -** 35 205 970 90

- min. recess depth mm
- max. recess depth mm


## WATER POINTS Concealed body spray FlowReduce - Light Gold

36 515 979

mm [inches]



Flow rate chart



Trajectory diagram



### Codes & Standards

DIN 4109

ISO 3822

Ü-Zeichen



## WATER POINTS Concealed body spray FlowReduce - Light Gold

---

36 515 979

Certificates

---

LGA\_18

## WATER POINTS Concealed body spray FlowReduce - Light Gold

36 515 979

