

36 501 979



- cover plate Ø 124 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS 2011026

	Dark Chrome	36 501 979-19
	Chrome	36 501 979-00
	Brushed Platinum	36 501 979-06
	Platinum	36 501 979-08
	Durabress (23kt Gold)	36 501 979-09
	Light Gold	36 501 979-26
	Brushed Light Gold	36 501 979-27
	Brushed Durabress (23kt Gold)	36 501 979-28
	Matte Black	36 501 979-33
	Brushed Bronze	36 501 979-42
	Brushed Champagne (22kt Gold)	36 501 979-46
	Champagne (22kt Gold)	36 501 979-47
	Brushed Chrome	36 501 979-93
	Brushed Dark Platinum	36 501 979-99


Required miscellaneous




xTOOL Concealed thermostat module without volume control - 35 503 970 90
 •max. recess depth 110 mm
 •min. recess depth 85 mm

36 501 979

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

EN 1111

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen



xTOOL Concealed thermostat without volume control 1/2" - Dark Chrome

META


36 501 979

Certificates

LGA_29

DVGW_DW-
6512DN0

WRAS_2011





36 501 979

Spare parts list