




xTOOL Concealed thermostat without volume control 1/2" - Brushed Bronze

SERIES SPECIFIC

36 501 979 Product version from 9/1/2022



- cover plate Ø 124 mm
- temperature control handle with safety limit stop at 38°C
- thermostat cartridge
- WRAS

| | | |
|---|--------------------------------|---------------|
|  | Brushed Bronze | 36 501 979-42 |
|  | Chrome | 36 501 979-00 |
|  | Brushed Platinum | 36 501 979-06 |
|  | Platinum | 36 501 979-08 |
|  | Durabronze (23kt Gold) | 36 501 979-09 |
|  | Dark Chrome | 36 501 979-19 |
|  | Light Gold | 36 501 979-26 |
|  | Brushed Light Gold | 36 501 979-27 |
|  | Brushed Durabronze (23kt Gold) | 36 501 979-28 |
|  | Matte Black | 36 501 979-33 |
|  | Brushed Dark Brass | 36 501 979-39 |
|  | Brushed Champagne (22kt Gold) | 36 501 979-46 |
|  | Champagne (22kt Gold) | 36 501 979-47 |
|  | Brushed Chrome | 36 501 979-93 |
|  | Brushed Dark Platinum | 36 501 979-99 |

Required miscellaneous



xTOOL Concealed thermostat module without volume control -

35 503 970 90

- min. recess depth 85 mm
- max. recess depth 110 mm
- integrated pre-seals

36 501 979 Product version from 9/1/2022

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

EN 1111

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen



xTOOL Concealed thermostat without volume control 1/2" - Brushed Bronze

SERIES SPECIFIC

36 501 979 Product version from 9/1/2022

Certificates and sustainability

| | | |
|-----------|---------------------|--------|
| WRAS_2011 | DVGW_DW- 6512DN0 | LGA_29 |
|-----------|---------------------|--------|

