

## AQUAMOON Concealed ceiling installation box with color light -

---

35 625 970 90




- concealed rough parts
- Rain panel with 3 different flow modes
- AQUACIRCLE RAIN: Circular rain curtain, max. flow rate 12 l/min (at 3 bar)
- TEMPEST RAIN: Natural rain, max. flow rate 10 l/min (at 3 bar)
- QUEEN'S COLLAR CASCADE: Rounded cascade, max. flow rate 24 l/min (at 3 bar)
- Ceiling installation enclosure 1356 x 1356 x 290 mm
- Opening diameter 1252 mm
- Ceiling construction with adequate structural strength for the permanent attachment of the device (weight: 57.5 kg / 127 lbs. (US)). M8 threaded bolts (minimum strength: 2000 N) are required to secure the ceiling module

To be provided by the customer. Zigbee Gateway!

AQUAMOON Concealed ceiling installation box with color light -

---

35 625 970 90



Codes & Standards

---

DIN 4109

ISO 3822

Ü-Zeichen


Certificates

---

LGA\_29

## AQUAMOON Concealed ceiling installation box with color light -

35 625 970 90





AQUAMOON Concealed ceiling installation box with color light -

35 625 970 90

Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
	04 24 03 239 02 90	fixing set	18	2