

41 771 979



exposed trim parts
 Rain panel with 2 different spray modes
PURIFY RAIN, 175 x 175 mm, max. flow rate 10 l/min (at 3 bar)
 FULL RAIN, 455 x 315 mm, max. flow rate 14 l/mi (at 3 bar)
 Rain panel, 600 x 420 mm
• min. recess depth 150 mm
• weight 15kg
feed pipe (hot/cold): 2x DN 20
with anti-scale system
 Recommended control element: xTool
electrical:

- RGBW LED ambient lighting
- Electricity supply: 100-240 V AC, 50-60 Hz, 20 W
- system of protection: IP 65
- Feeder 3 x 1.5 mm2 NYM-J
- equipotential bonding 1 x 4mm2
- earth-leakage circuit-breaker 30 mA provided
- Provide DIN VDE 0100, Part 701 compliant safety zone 2
 • Provided by customer: Zigbee gateway
- Not suitable for use in a steam room.

includes light bulbs with a Class G energy

includes light bulbs with a Class G energy efficiency

Required miscellaneous




SERENITY SKY Concealed ceiling 35 771 970 90 installation box with light -

- concealed rough parts
- •flush-mounted reflection box, 662 x
- 482 mm, RAL 9003, Signal White
- •2x female thread 1/2" connections
- •min. recess depth 150 mm
- •weight 15kg
- •Supply pipe 7 m
- •Input 100-240V AC 50-60Hz •Output 24V DC SELV / Class II
- •ZigBee Light Link RGBW controller
- •Provided by customer: Zigbee gateway






41 771 979



Flow rate chart





41 771 979



41 771 979

Spare parts list