

41 780 979



- exposed trim parts
- Rain panel with 5 different flow modes
- Rain panel, 600 x 420 mm
- \bullet PURIFY RAIN, 175 x 175 mm, max. flow rate 10 I/min (at 3 bar)
 • FULL RAIN, 455 x 315 mm, max. flow rate 14 I/min
- (at 3 bar) • LAMINAR FLOW, max. flow rate 10 l/min (at 3 bar)
- AQUAPRESSURE FLOW, max. flow rate 9.4 l/min
- COOL MIST, max. flow rate 1 l/min (at 3 bar)
- min. recess depth 150 mm
- weight 15kg
- feed pipe (hot/cold): 2x DN 20
- with anti-scale system
- Recommended control element: xTool
- Not suitable for use in a steam room.

n)	r	Dark Chrome	41 780 979-19
		Chrome	41 780 979-00
	٦	Brushed Bronze	41 780 979-42
		Brushed Champagne (22kt Gold)	41 780 979-46
		Champagne (22kt Gold)	41 780 979-47
		Brushed Stainless Steel	41 780 979-86
	٩	Brushed Dark Platinum	41 780 979-99

Required miscellaneous




SERENITY SKY+ Concealed ceiling installation box -


- 35 780 970 90
- •concealed rough parts
- •5x 1/2" female connector
- •flush-mounted reflection box, 662 x
- 482 mm, RAL 9003, Signal White
- •min. recess depth 150 mm
- •weight 15kg



41 780 979



Flow rate chart





41 780 979



41 780 979

Spare parts list