

WATER FALL Cascade spout for wall-mounted installation - Matte Black

SERIES-VARIOUS

13 420 979    Product version from 4/1/2023




- CASCADE, flow rate max. 7 gpm (at 3 bar)
- Function from: gpm

Technical data:

- Cover plate 9-1/2" x 2-3/8"
- 4-3/4" Projection
- 1/2" connection
- Plug-in connection mounting

	Matte Black	13 420 979-33
	Chrome	13 420 979-00
	Brushed Platinum	13 420 979-06
	Platinum	13 420 979-08
	Dark Chrome	13 420 979-19
	Light gold	13 420 979-26
	Brushed Light Gold	13 420 979-27
	Brushed Durabrass (23kt Gold)	13 420 979-28
	Brushed Dark Brass	13 420 979-39
	Brushed Bronze	13 420 979-42
	Brushed Champagne (22kt Gold)	13 420 979-46
	Champagne (22kt Gold)	13 420 979-47
	Brushed Chrome	13 420 979-93

Required article

	Rough-in adapter -	35 080 970-90 0010
-------------------------------------------------------------------------------------	--------------------	-----------------------

13 420 979 Product version from 4/1/2023

mm [inches]



**Flow rate chart**



**Trajectory length diagram**



## Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen



## WATER FALL Cascade spout for wall-mounted installation - Matte Black

SERIES-VARIOUS

13 420 979 Product version from 4/1/2023

### Certificates and sustainability

LGA\_18

IAPMO\_4976

WRAS\_2111



## Spare parts list

Number	Item Number	Designation	Number of units	Lead time
7	09 27 97 034-33	rosette	1.00	30
11	09 30 01 104-33	casing	1.00	30
13	09 11 94 046-33	spout	1.00	30
6	09 17 11 044 20 90	distributor	1.00	2
8	09 31 11 049 90	pin	4.00	2
2	09 17 97 056 90	holder	1.00	2
5	90 29 30 040 00 90	insert	1.00	2
3	90 24 05 008 00 90	nipple set	1.00	2
4	09 14 10 504 90	seal	1.00	2
1	04 30 31 024 01 90	fixing set	1.00	2
9	09 30 30 147 90	screw	2.00	2
10	09 30 30 086 90	screw	4.00	2
12	09 14 03 504 90	seal	1.00	2