

















WATER FALL Cascade spout with PEARLSTREAM for wall-mounted installation - Brushed Platinum

SERIES-VARIOUS

13 425 979    Product version from 10/1/2023



- Pearlstream
  - Flow rate max. 2.5 gpm (at 3 bar)
  - Function from: gpm
- Technical data:**
- Plate 9-1/2" x 2-3/8"
  - 7/8" Projection
  - Connection 1/2", can be cut to length
  - Plug-in connection mounting

	Brushed Platinum	13 425 979-06
	Chrome	13 425 979-00
	Platinum	13 425 979-08
	Dark Chrome	13 425 979-19
	Light gold	13 425 979-26
	Brushed Light Gold	13 425 979-27
	Brushed Durabrass (23kt Gold)	13 425 979-28
	Matte Black	13 425 979-33
	Brushed Dark Brass	13 425 979-39
	Brushed Bronze	13 425 979-42
	Brushed Champagne (22kt Gold)	13 425 979-46
	Champagne (22kt Gold)	13 425 979-47
	Brushed Chrome	13 425 979-93
	Brushed Dark Platinum	13 425 979-99

Required article

Rough-in adapter -


35 080 970-90  
0010




# WATER FALL Cascade spout with PEARLSTREAM for wall-mounted installation - Brushed Platinum

SERIES-VARIOUS

13 425 979 Product version from 10/1/2023  
mm [inches]



Flow rate chart



Trajectory length diagram



## Codes & Standards

ASME A112.18.1

cUPC

DIN 4109

ISO 3822

Ü-Zeichen



## WATER FALL Cascade spout with PEARLSTREAM for wall-mounted installation - Brushed Platinum

SERIES-VARIOUS

---

13 425 979 Product version from 10/1/2023

Certificates and sustainability

---


LGA\_19

IAPMO\_4976

## WATER FALL Cascade spout with PEARLSTREAM for wall-mounted installation - Brushed Platinum

SERIES-VARIOUS

13 425 979 Product version from 10/1/2023



### Spare parts list

Number	Item Number	Designation	Number of units	Lead time
6	09 31 11 144 90	pin	2.00	2
1	04 30 31 024 01 90	fixing set	1.00	2
8	90 29 03 071 00 90	insert	1.00	2
2	09 14 05 009 90	seal	1.00	2
3	09 17 97 053 90	holder	1.00	2
5	90 31 20 087 00-06	plug	1.00	10
4	90 24 03 199 00 90	connection	1.00	2