

## Rain shower flush mounted 11-3/4" x 9-1/2" - Brushed Champagne (22kt Gold) SERIES SPECIFIC

28 043 980 Product version from 5/1/2022



- 11-3/4" x 9-1/2" Rain showerhead
- PURE RAIN, flow rate max. 1.8 gpm (at 3 bar)
- PURIFY RAIN, flow rate max. 1.6 gpm (at 3 bar)
- Min. rough in depth 5-3/8"
- Descaling system
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- Not suitable for use in a steam room.

**To meet the North American plumbing standards, this application must be installed with a diverter (rough included).**

To meet the North American plumbing standards, this application must be installed with a diverter (rough included).

	Brushed Champagne (22kt Gold)	28 043 980-46 0010
	Chrome	28 043 980-00 0010
	Brushed Platinum	28 043 980-06 0010
	Platinum	28 043 980-08 0010
	Dark Chrome	28 043 980-19 0010
	Brushed Light Gold	28 043 980-27 0010
	Brushed Durabrass (23kt Gold)	28 043 980-28 0010
	Matte Black	28 043 980-33 0010
	Champagne (22kt Gold)	28 043 980-47 0010
	Brushed Chrome	28 043 980-93 0010
	Brushed Dark Platinum	28 043 980-99 0010

### Required article



- Installation rough flush mounted - 35 043 970-90 0010**
- Installation depth 5-3/8"
  - Pre-assembly kit for three-way diverter included




Rain shower flush mounted 11-3/4" x 9-1/2" - Brushed Champagne (22kt Gold) SERIES SPECIFIC

---

28 043 980    Product version from 5/1/2022

mm [inches]



Codes & Standards

---

ASME A112.18.1	California Energy Commission (CEC)	cUPC	EPA WaterSense
----------------	------------------------------------	------	----------------


WaterSense



Certificates and sustainability

---

IAPMO_4976	IAPMO_11777
------------	-------------



Spare parts list

Number	Item Number	Designation	Number of units	Lead time
1	90 17 20 260 00 90	flange	1.00	2
2	90 24 03 309 02 90	connection	1.00	2