







28 508 360



- Ø 3-3/4"
- 3-way adjustable: COMPACT RAIN, COMPACT SOFT FLOW, COMPACT AQUAPRESSURE FLOW, flow rate max. 2 gpm (at 3 bar)
- Function from: gpm
- Descaling system

Technical dimensions:

- 7-7/8" Projection
- Ball-joint pivotable through 30°
- Flange diameter 2-1/8"
- 1/2" connection

	Brushed Platinum	28 508 360-06 0010
	Chrome	28 508 360-00 0010
	Platinum	28 508 360-08 0010
	Durabrand (23kt Gold)	28 508 360-09 0010
	Brushed Durabrand (23kt Gold)	28 508 360-28 0010
	Brushed Dark Platinum	28 508 360-99 0010

28 508 360

mm [inches]



Codes & Standards

DIN 4109

ISO 3822


Ü-Zeichen

Certificates and sustainability

LGA_38

28 508 360

Parts for other
 finishes can be found
 here: [Chrome](#)



Spare parts list

Number	Item Number	Designation	Number of units	Lead time
4	04 12 11 120 01-06	shower	1.00	10
3	09 11 03 011-06	connection	1.00	10
1	09 27 35 003-06	rosette	1.00	10
2	90 14 10 026 00 90	seal	1.00	2