

## IMO Three-hole single-lever bath mixer for bath rim or tile edge installation - Matte Black

IMO







27 412 670



- 224mm projection
- spout: cascade
- max. flow 19.2 l/min at 3 bar flow pressure
- Hand shower: COMPACT RAIN, max. flow rate 6.8 l/min (at 3 bar)
- complete hand shower set with anti-scale system
- automatic bath/shower diverter
- height of mixer 110 mm
- height up to aerator 138 mm
- hole diameter spout 32 mm
- single-lever mixer hole diameter 35 mm
- hole diameter for complete hand shower set 32 mm
- rosette for mixer 60 x 60mm
- rosette for spout 60 x 60mm
- rosette for complete hand shower set 60 x 60mm
- metal shower hose 2250mm with integrated anti-twist protection

Note: Local building codes may require the use of an anti-scald device. Please refer to remote pressure balance valve (35 910 970 90)

Intrinsic protection against back flow.


	Matte Black	27 412 670-33
	Chrome	27 412 670-00
	Brushed Platinum	27 412 670-06
	Dark Chrome	27 412 670-19
	Brushed Light Gold	27 412 670-27
	Brushed Chrome	27 412 670-93

## IMO Three-hole single-lever bath mixer for bath rim or tile edge installation - Matte Black


IMO

27 412 670

mm [inches]



### Flow rate chart



### Codes & Standards

ASME A112.18.1

ASME  
A112.18.1/CSA  
B125.1

California Energy  
Commission  
(CEC)

cUPC

EN 1717



## IMO Three-hole single-lever bath mixer for bath rim or tile edge installation - Matte Black

---

IMO

27 412 670

Certificates

---


Belgaqua\_24-008-2 IAPMO\_4976

## IMO Three-hole single-lever bath mixer for bath rim or tile edge installation - Matte Black

IMO

27 412 670

Parts for other  
finishes can be found  
here: [Chrome](#)





## IMO Three-hole single-lever bath mixer for bath rim or tile edge installation - Matte Black

---

IMO

27 412 670

### **Spare parts list**