







CL.1 Wall-mounted basin mixer without pop-up waste - Brushed Platinum

CL.1

ST 010 201 0705



- 200mm projection
- fixed spout
- rectangular spray pattern with 40 individual jets
- hole diameter valve 35 mm
- hole diameter spout 40 mm
- rosette 60 x 60 mm
- max. flow 4.5 l/min
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

	Brushed Platinum	ST 010 201 0705-06
	Chrome	ST 010 201 0705-00
	Dark Chrome	ST 010 201 0705-19
	Brushed Champagne (22kt Gold)	ST 010 201 0705-46
	Champagne (22kt Gold)	ST 010 201 0705-47
	Brushed Dark Platinum	ST 010 201 0705-99

Individual components of this set

You need the following components for this set

1x 13 800 705-06



1x 36 607 706-06



1x 36 607 707-06









CL.1 Wall-mounted basin mixer without pop-up waste - Brushed Platinum

CL.1

ST 010 201 0705



- 200mm projection
- fixed spout
- rectangular spray pattern with 40 individual jets
- hole diameter 37 mm
- lead-free
- 1/2" connection
- plug-link mounting
- max. flow 4.5 l/min
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS 1512013

	Brushed Platinum	13 800 705-0
	Chrome	13 800 705-0
	Dark Chrome	13 800 705-1
	Brushed Champagne (22kt Gold)	13 800 705-4
	Champagne (22kt Gold)	13 800 705-4
	Brushed Dark Platinum	13 800 705-9


CL.1 Wall-mounted basin mixer without pop-up waste - Brushed Platinum

CL.1

ST 010 201 0705


6
—
0
—
9
—
6
—
7
—
9
—

Required miscellaneous


	Concealed adapter -	35 080 970-90 0010
		

ST 010 201 0705


mm [inches]



Flow rate chart



Codes & Standards

ASME A112.18.1	ASME A112.18.1/CSA B125.1	California Energy Commission (CEC)	cUPC
DIN 4109	EPA WaterSense	ISO 3822	NSF/ANSI 372
NSF/ANSI/CAN 61	NSF372	NSF61	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen	Water Sense	WaterSense 



CL.1 Wall-mounted basin mixer without pop-up waste - Brushed Platinum


CL.1

ST 010 201 0705

Certificates

IAPMO_N-4	IAPMO_8834	LGA_28	IAPMO_6	WRAS_1512
IAPMO_4976				

Product version from 3/9/2015



ST 010 201 0705

Spare parts list

Product version from 3/9/2015

No.	Item Number	Name	Quantity used	Delivery time
	09 24 03 081 10 90	extension	10	2







CL.1 Wall-mounted basin mixer without pop-up waste - Brushed Platinum

CL.1

ST 010 201 0705



- rosette 60 x 60 mm
- with cold marking
- head part with cut-to-length spindle and sleeve
- WRAS 2010066

	Brushed Platinum	36 607 706-0
	Chrome	36 607 706-0
	Dark Chrome	36 607 706-1
	Brushed Champagne (22kt Gold)	36 607 706-4
	Champagne (22kt Gold)	36 607 706-4
	Brushed Dark Platinum	36 607 706-9

ST 010 201 0705

6

—

10

—

9

—

6

—


7

—

9


—

Required miscellaneous

	Wall valve 1/2" -	35 607 970-90
	•max. recess depth 150 mm	0010
	•min. recess depth 105 mm	

ST 010 201 0705

mm [inches]



Certificates


IAPMO_4976	DVGW_DW-6501DN0	WRAS_2010	LGA_29	LGA_29
------------	-----------------	-----------	--------	--------

Codes & Standards			
ADA	ASME A112.18.1	ASME A112.18.1/CSA B125.1	cUPC
DIN 4109	EN 200	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		

ST 010 201 0705

Product version up to 10/14/2020

Product version from 10/14/2020



ST 010 201 0705

Spare parts list

Product version up to 10/14/2020

Product version from 10/14/2020

No.	Item Number	Name	Quantity used	Delivery time
	90 20 70 051 02-06	handle (cold)	3	10







CL.1 Wall-mounted basin mixer without pop-up waste - Brushed Platinum

CL.1

ST 010 201 0705




- rosette 60 x 60 mm
- with hot marking
- head part with cut-to-length spindle and sleeve
- WRAS 2010066

	Brushed Platinum	36 607 707-0
	Chrome	36 607 707-0
	Dark Chrome	36 607 707-1
	Brushed Champagne (22kt Gold)	36 607 707-4
	Champagne (22kt Gold)	36 607 707-4
	Brushed Dark Platinum	36 607 707-9

ST 010 201 0705

6
—
0
—
9
—
6
—
7
—
9
—

Required miscellaneous

	Wall valve 1/2" -	35 607 970-90
	•max. recess depth 150 mm	0010
	•min. recess depth 105 mm	

ST 010 201 0705

mm [inches]



Certificates


IAPMO_4976	DVGW_DW-6501DN0	WRAS_2010	LGA_29	LGA_29
------------	-----------------	-----------	--------	--------

Codes & Standards			
ADA	ASME A112.18.1	ASME A112.18.1/CSA B125.1	cUPC
DIN 4109	EN 200	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		

ST 010 201 0705

Product version up to 10/14/2020

Product version from 10/14/2020



ST 010 201 0705

Spare parts list

Product version up to 10/14/2020

Product version from 10/14/2020

No.	Item Number	Name	Quantity used	Delivery time
	90 20 70 051 03-06	handle (hot)	3	10