

### Rain shower for surface-mounted ceiling installation 300 mm - Brushed Dark **Platinum**

**TARA** 

28 031 970



Fits: TARA, LISSÉ, VAIA, META

- rain shower Ø 300 mm
- PURE RAIN, max. flow rate 6.8 l/min (at 3 bar)
- PURIFY RAIN, max. flow rate 6 l/min (at 3 bar)
- Distance to ceiling from bottom edge of shower 40 mm
  • with anti-scale system

Three-way diverter ensures that the product does not exceed the max. flow rate of 2.5 gpm at any setting. It does not permit the use of two functions simultaneously.

Three-way diverter trim is sold separately

Pre-assembly kit for three-way diverter included

Three-way diverter ensures that the product does not exceed the max. flow rate of 2.5 gpm at any setting. It does not permit the use of two functions simultaneously.

Three-way diverter trim is sold separately

Pre-assembly kit for three-way diverter included

	Brushed Dark Platinum	28 031 970-99 0010
	Chrome	28 031 970-00 0010
	Brushed Platinum	28 031 970-06 0010
•	Platinum	28 031 970-08 0010
	Dark Chrome	28 031 970-19 0010
	Light Gold	28 031 970-26 0010
	Brushed Light Gold	28 031 970-27 0010
	Brushed Durabrass (23kt Gold)	28 031 970-28 0010
	Matte Black	28 031 970-33 0010
	Brushed Bronze	28 031 970-42 0010
	Brushed Champagne (22kt Gold)	28 031 970-46 0010
	Champagne (22kt Gold)	28 031 970-47 0010
	Brushed Chrome	28 031 970-93 0010

#### Required miscellaneous



Concealed ceiling installation box 35 041 970-90 for surface-mounted ceiling installation -

- •max. recess depth 115 mm
- •min. recess depth 90 mm
- Pre-assembly kit for three-way

diverter included







# Rain shower for surface-mounted ceiling installation 300 mm - Brushed Dark Platinum

28 031 970 mm [inches]





#### Flow rate chart



#### Codes & Standards

California Energy Commission (CEC) Water Sense





# Rain shower for surface-mounted ceiling installation 300 mm - Brushed Dark Platinum

TARA

28 031 970 Certificates


IAPMO\_11777. IAPMO\_4976 (7).





# Rain shower for surface-mounted ceiling installation 300 mm - Brushed Dark Platinum

28 031 970



### Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 17 20 263 00 90	fixing set	1	2
2	90 24 03 309 02 90	connection	2	2