



Rain shower for surface-mounted ceiling installation 300 mm - Champagne (22kt Gold)
SERIES SPECIFIC

28 031 970    Product version from 5/1/2022



- rain shower Ø 300 mm
  - PURE RAIN, max. flow rate 12 l/min (at 3 bar)
  - PURIFY RAIN, max. flow rate 6 l/min (at 3 bar)
  - with anti-scale system
- Technical data:**
- Distance to ceiling from bottom edge of shower 40 mm
  - For simultaneous control of the jet types, we recommend the xTool thermostat module
  - WRAS

	Champagne (22kt Gold)	28 031 970-47
	Chrome	28 031 970-00
	Brushed Platinum	28 031 970-06
	Platinum	28 031 970-08
	Dark Chrome	28 031 970-19
	Light Gold	28 031 970-26
	Brushed Light Gold	28 031 970-27
	Brushed Durabrass (23kt Gold)	28 031 970-28
	Matte Black	28 031 970-33
	Brushed Dark Brass	28 031 970-39
	Brushed Bronze	28 031 970-42
	Brushed Champagne (22kt Gold)	28 031 970-46
	Brushed Chrome	28 031 970-93
	Brushed Dark Platinum	28 031 970-99

Required miscellaneous




- Concealed ceiling installation box    35 041 970 90**  
**with ceiling fixing -**
- concealed rough parts
  - min. recess depth 90 mm
  - max. recess depth 115 mm
  - 2x female thread " outlet


# Rain shower for surface-mounted ceiling installation 300 mm - Champagne (22kt Gold)

SERIES SPECIFIC

28 031 970 Product version from 5/1/2022  
mm [inches]



## Flow rate chart



## Codes & Standards

DIN 4109

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen



## Rain shower for surface-mounted ceiling installation 300 mm - Champagne (22kt Gold)

SERIES SPECIFIC

---


28 031 970 Product version from 5/1/2022

Certificates and sustainability

---

LGA\_38

WRAS\_240502



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
1	90 17 20 263 00 90	fixing set	1.00	2
2	90 24 03 309 01 90	connection	1.00	2
3	90 24 03 309 00 90	connection	1.00	2