

TARA ULTRA Profi single-lever mixer - Brushed Chrome








TARA ULTRA

33 860 875 Product version from 5/2/2022



- 240mm projection
- pivotable 360°
- air-enriched flow and spray flow
- height of mixer 685 mm
- height up to aerator 129 mm
- hole diameter 35 mm
- sprayface with anti-scaling system
- max. flow 8 l/min at 3 bar flow pressure
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

Intrinsic protection against back flow.

| | | |
|---|-----------------------|---------------|
|  | Brushed Chrome | 33 860 875-93 |
|  | Chrome | 33 860 875-00 |
|  | Brushed Platinum | 33 860 875-06 |
|  | Platinum | 33 860 875-08 |
|  | Dark Chrome | 33 860 875-19 |
|  | Brushed Bronze | 33 860 875-42 |
|  | Brushed Dark Platinum | 33 860 875-99 |

Recommended miscellaneous

Strainer waste with control handle 10 712 970-93
- Brushed Chrome





Flow rate chart



Codes & Standards

DIN 4109

EN 1717

ISO 3822

Ü-Zeichen



TARA ULTRA Profi single-lever mixer - Brushed Chrome

TARA ULTRA

33 860 875 Product version from 5/2/2022

Certificates and sustainability

LGA_18

Belgaqua_22_277_2

33 860 875 Product version from 5/2/2022

Parts for other
finishes can be found
here: [Chrome](#)

