

Concealed thermostat with two function volume control - Dark Chrome

SERIES SPECIFIC

36 426 970



- rotary diverter with volume control and shut-off function
- cover plate Ø 150 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset
- WRAS

| | | |
|--|--------------------------------|---------------|
| | Dark Chrome | 36 426 970-19 |
| | Chrome | 36 426 970-00 |
| | Brushed Platinum | 36 426 970-06 |
| | Platinum | 36 426 970-08 |
| | Light Gold | 36 426 970-26 |
| | Brushed Light Gold | 36 426 970-27 |
| | Brushed Durabronze (23kt Gold) | 36 426 970-28 |
| | Matte Black | 36 426 970-33 |
| | Brushed Dark Brass | 36 426 970-39 |
| | Brushed Bronze | 36 426 970-42 |
| | Brushed Champagne (22kt Gold) | 36 426 970-46 |
| | Champagne (22kt Gold) | 36 426 970-47 |
| | Brushed Chrome | 36 426 970-93 |
| | Brushed Dark Platinum | 36 426 970-99 |

Required miscellaneous



Concealed thermostat with built-in isolators - 35 426 970 90
 • max. recess depth 136 mm
 • min. recess depth 80 mm

Recommended miscellaneous



xGRID Attachment set for integrating in the dry wall construction - 12 340 970 90

Required miscellaneous



Concealed thermostat - 35 425 970 90
 • max. recess depth 136 mm
 • min. recess depth 80 mm

Required miscellaneous



xGRID Installation track 555 mm - 12 360 970 90

36 426 970

mm [inches]



Flow rate chart



Codes & Standards

| | | | |
|-----------------------------|-----------|------------|------------------------|
| DIN 4109 | EN 1111 | ISO 3822 | Scottish Water Byelaws |
| UK Water Supply Regulations | Ü-Zeichen | VA-Zeichen | |



Concealed thermostat with two function volume control - Dark Chrome

SERIES SPECIFIC

36 426 970

Certificates and sustainability

| | | | | |
|--------|--------|-----------------|--------|-------------|
| LGA_19 | ETA_20 | DVGW_DW-6512DN0 | LGA_19 | WRAS_250402 |
|--------|--------|-----------------|--------|-------------|

36 426 970

