

Concealed thermostat with three function volume control - Brushed Champagne (22kt Gold) SERIES SPECIFIC

36 427 970 Product version from 6/30/2022



- rotary diverter with volume control and shut-off function
- cover plate Ø 150 mm
- temperature control handle with safety limit stop at 38°C
- hot water temperature limiter, can be preset
- WRAS

	Brushed Champagne (22kt Gold)	36 427 970-46
	Chrome	36 427 970-00
	Brushed Platinum	36 427 970-06
	Platinum	36 427 970-08
	Dark Chrome	36 427 970-19
	Light Gold	36 427 970-26
	Brushed Light Gold	36 427 970-27
	Brushed Durabronze (23kt Gold)	36 427 970-28
	Matte Black	36 427 970-33
	Brushed Bronze	36 427 970-42
	Champagne (22kt Gold)	36 427 970-47
	Brushed Chrome	36 427 970-93
	Brushed Dark Platinum	36 427 970-99

Required miscellaneous



- Concealed thermostat -** 35 427 970 90
- max. recess depth 136 mm
 - min. recess depth 80 mm

Recommended miscellaneous



- xGRID Attachment set for integrating in the dry wall construction -** 12 340 970 90

Required miscellaneous



- Concealed thermostat with built-in isolators -** 35 428 970 90
- max. recess depth 136 mm
 - min. recess depth 80 mm


Required miscellaneous




- xGRID Installation track 555 mm -** 12 360 970 90

Concealed thermostat with three function volume control - Brushed Champagne SERIES SPECIFIC (22kt Gold)

36 427 970 Product version from 6/30/2022
mm [inches]



Flow rate chart



Codes & Standards

DIN 4109	EN 1111	ISO 3822	Scottish Water Byelaws
UK Water Supply Regulations	Ü-Zeichen		



Concealed thermostat with three function volume control - Brushed Champagne SERIES SPECIFIC
(22kt Gold)

36 427 970 Product version from 6/30/2022

Certificates and sustainability

LGA_29	DVGW_DW- 6512DN0	WRAS_250402
--------	---------------------	-------------

Concealed thermostat with three function volume control - Brushed Champagne SERIES SPECIFIC (22kt Gold)

36 427 970 Product version from 6/30/2022

