



- exposed trim parts
- Rain panel with 3 different flow modes
- AQUACIRCLE RAIN: Circular rain curtain, max. flow rate 14 l/min (at 3 bar)
- TEMPEST RAIN: Natural rain, max. flow rate 9 l/min (at 3 bar)
- DIAMOND RAIN: Ring of rain, max. flow rate 6.8 l/min (at 3 bar)

## Technical data:

- Outer diameter: 605 mm, opening diameter: 465 mm
- Weight: 6 kg

## Electric:

### Separate LED power supply

- 350mA (CC)

### Input LED power supply

- 350mA (CC)
- Input 100-240V AC 50-60Hz
- Technology: LED, not dimmable

### Spot lighting

### Output LED power supply

### Output specification LED power supply

- IP67
- SELV (Safety Extra Low Voltage)
- Class 2

### Ceiling module power supply

- Supply pipe 7 m
- LED colour temperature approx. 3000 K
- Bulbs protected against splashing water
- Provided by customer: Light switch

## Environment






### Planning tips:

- Not suitable for outdoor use.
- Not suitable for use in a steam room.
- Not suitable for use in chlorinated or salty environments.
- Comply with the protection zone regulations as defined in DIN VDE 0100, Part 701 (IEC 60364-7-701).

### Notes:

- Recommended control element: xTool
- Contains energy efficiency class bulbs

Pre-assembly kit for three-way diverter included

|   |                               |               |
|---|-------------------------------|---------------|
|  | Brushed Platinum              | 41 750 979-06 |
|  | Chrome                        | 41 750 979-00 |
|  | Matte Black                   | 41 750 979-33 |
|  | Brushed Champagne (22kt Gold) | 41 750 979-46 |
|  | Champagne (22kt Gold)         | 41 750 979-47 |

**Required miscellaneous**



**SERIES-VARIOUS AQUAHALO 35 750 970-06  
Concealed ceiling installation box  
- Brushed Platinum**

- concealed rough parts
- Ceiling installation enclosure 605 x 605 x 95 mm
- Weight: 10 kg
- min. recess depth 110 mm
- Pre-assembly kit for three-way diverter included

41 750 979 Product version from 4/1/2024



### Flow rate chart



### Codes & Standards

DIN 4109

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

Ü-Zeichen



SERIES-VARIOUS AQUAHALO Rain panel - Brushed Platinum

SERIES-VARIOUS

41 750 979 Product version from 4/1/2024

Certificates and sustainability

LGA\_38 WRAS\_250302

41 750 979 Product version from 4/1/2024

Parts for other  
finishes can be found  
here: [Chrome](#)



## Spare parts list

| No. | Item Number        | Name               | Quantity used | Delivery time |
|-----|--------------------|--------------------|---------------|---------------|
| 1   | 90 28 22 605 01-06 | distributor        | 4.00          | 10            |
| 2   | 90 12 05 087 00-06 | casing             | 1.00          | 10            |
| 3   | 90 24 03 535 01 90 | distributor        | 2.00          | 2             |
| 5   | 90 24 04 384 00 90 | adaptor            | 20.00         | 2             |
| 9   | 90 30 03 117 00 90 | hose               | 1.00          | 2             |
| 10  | 90 17 09 061 01 90 | jet module TEMPEST | 8.00          | 2             |
| 8   | 90 30 03 118 00 90 | hose               | 1.00          | 2             |
| 4   | 90 17 09 060 01 90 | jet module         | 12.00         | 2             |
| 6   | 90 12 05 088 00-06 | casing             | 1.00          | 10            |
| 7   | 90 24 03 535 00 90 | distributor        | 2.00          | 2             |