

# META Washstand fitting with electronic opening and closing function without pop-up waste - Dark Chrome

META

44 515 660



- Infrared sensor technology
- 125mm projection
- height of mixer 140 mm
- height up to aerator 52 mm
- hole diameter 35 mm
- fixed spout
- max. flow 5.7 l/min
- circular, air-enriched flow
- suitable for thermal disinfection
- Automatic shut-off after pre-set time is reached
- Direct temperature control at faucet
- Battery-powered (batteries not included)
- 1x CR-P2 battery required
- lead-free
- 2x screw-in M 8 x 1 pressure hose, leak-tested
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB
- WRAS

Batteries not included


	Dark Chrome	44 515 660-19
	Chrome	44 515 660-00
	Brushed Platinum	44 515 660-06
	Platinum	44 515 660-08
	Light Gold	44 515 660-26
	Brushed Light Gold	44 515 660-27
	Matte Black	44 515 660-33
	Brushed Bronze	44 515 660-42
	Brushed Champagne (22kt Gold)	44 515 660-46
	Champagne (22kt Gold)	44 515 660-47
	Brushed Chrome	44 515 660-93
	Brushed Dark Platinum	44 515 660-99

# META Washstand fitting with electronic opening and closing function without pop-up waste - Dark Chrome

META

44 515 660

mm [inches]



## Flow rate chart



## Codes & Standards

DIN 4109

ISO 3822

Scottish Water  
Byelaws

UK Water Supply  
Regulations

## Ü-Zeichen



## META Washstand fitting with electronic opening and closing function without pop-up waste - Dark Chrome

---

META

44 515 660

Certificates and sustainability

---

LGA\_38

WRAS\_2212

# META Washstand fitting with electronic opening and closing function without pop-up waste - Dark Chrome

META

44 515 660  
Parts for other  
finishes can be found  
here: [Chrome](#)

