



TARA ULTRA COLD WATER DISPENSER - Platinum

17 872 875



- 146mm projection
- pivotable spout 360°
- laminar flow
- height of mixer 290 mm
- height up to laminar flow regulator 182 mm
- hole diameter 35 mm
- Provides filtered, cold water or filtered, chilled water (depending on your combination)

 • max. flow 3.8 l/min at 3 bar flow pressure
- mechanical valve
- lead-free
- This product can help a building meet the requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

Compatible with standard filtration systems or chillers with $\frac{1}{4}$ " compression connection.

In addition, the installation must be above a kitchen

The filter cartridge must be changed every six months. The installation instructions contain further information for guidance.

Detailed planning information and technical data can be found at www.dornbracht.com/professional

Available for delivery from the fourth quarter of 2024.

| | Platinum | 17 872 875-08 |
|---|-------------------------------------|---------------|
| | Chrome | 17 872 875-00 |
| | Brushed Platinum | 17 872 875-06 |
| | Dark Chrome | 17 872 875-19 |
| | Brushed Durabrass (23kt Gold) | 17 872 875-28 |
| | Matte Black | 17 872 875-33 |
| 1 | Brushed Champagne (22kt Gold) | 17 872 875-46 |
| | Champagne (22kt Gold) | 17 872 875-47 |
| | Brushed Chrome | 17 872 875-93 |
| | Brushed Dark Platinum | 17 872 875-99 |



TARA ULTRA COLD WATER DISPENSER - Platinum

17 872 875

