

Hand shower set with integrated shower holder - Brushed Bronze



























SERIES SPECIFIC

27 803 660 Product version from 6/3/2020



- COMPACT RAIN, max. flow rate 15 l/min (at 3 bar)
- three settings: normal flow, soft flow, massage flow
- with anti-scale system
- 3/8" shower outlet
- metal shower hose 1250mm with integrated anti-twist protection
- rosette Ø 60 mm
- 1/2" connection
- Function from: 7 l/min
- WRAS

Intrinsic protection against back flow.



	Brushed Bronze	27 803 660-42
	Chrome	27 803 660-00 0010
	Chrome	27 803 660-00
	Brushed Platinum	27 803 660-06 0010
	Brushed Platinum	27 803 660-06
	Platinum	27 803 660-08
	Platinum	27 803 660-08 0010
	Dark Chrome	27 803 660-19
	Dark Chrome	27 803 660-19 0010
	Light Gold	27 803 660-26 0010
	Light Gold	27 803 660-26
	Brushed Light Gold	27 803 660-27 0010
	Brushed Light Gold	27 803 660-27
	Brushed Durabrass (23kt Gold)	27 803 660-28 0010
	Brushed Durabrass (23kt Gold)	27 803 660-28
	Matte Black	27 803 660-33 0010
	Matte Black	27 803 660-33
	Brushed Dark Brass	27 803 660-39
	Brushed Dark Brass	27 803 660-39 0010
	Brushed Bronze	27 803 660-42 0010
	Brushed Champagne (22kt Gold)	27 803 660-46
	Brushed Champagne (22kt Gold)	27 803 660-46 0010
	Champagne (22kt Gold)	27 803 660-47
	Champagne (22kt Gold)	27 803 660-47 0010
	Brushed Chrome	27 803 660-93
	Brushed Chrome	27 803 660-93 0010

Hand shower set with integrated shower holder - Brushed Bronze


SERIES SPECIFIC

27 803 660


Product version from 6/3/2020

	Brushed Dark Platinum	27 803 660-99
	Brushed Dark Platinum	27 803 660-99 0010

Recommended miscellaneous

	Concealed wall elbow - •min. recess depth 90 mm •max. recess depth 163 mm	35 085 970 90
---	--	---------------

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

EN 1717

ISO 3822

Scottish Water
Byelaws

UK Water Supply
Regulations

Ü-Zeichen



Hand shower set with integrated shower holder - Brushed Bronze

SERIES SPECIFIC

27 803 660 Product version from 6/3/2020

Certificates and sustainability

LGA_29

Belgaqua_24-007-2 WRAS_250402

