

TARA Hand shower set with individual rosettes - Brushed Platinum

TARA

27 803 892 Product version from 6/30/2015 to 7/21/2020



- COMPACT RAIN, max. flow rate 15 l/min (at 3 bar)
- three settings: normal flow, soft flow, massage flow
- with anti-scale system
- 1/2" shower outlet
- rosette for wall elbow Ø 55mm
- rosette for shower holder Ø 55mm
- metal shower hose 1250mm with integrated anti-twist protection
- 1/2" wall elbow

Intrinsic protection against back flow.

	Brushed Platinum	27 803 892-06
	Chrome	27 803 892-00
	Chrome	27 803 892-00 0010
	Brushed Platinum	27 803 892-06 0010
	Platinum	27 803 892-08
	Platinum	27 803 892-08 0010
	Dark Chrome	27 803 892-19
	Dark Chrome	27 803 892-19 0010
	Brushed Durabronze (23kt Gold)	27 803 892-28 0010
	Brushed Durabronze (23kt Gold)	27 803 892-28
	Matte Black	27 803 892-33
	Matte Black	27 803 892-33 0010
	Brushed Bronze	27 803 892-42
	Brushed Bronze	27 803 892-42 0010
	Brushed Champagne (22kt Gold)	27 803 892-46 0010
	Brushed Champagne (22kt Gold)	27 803 892-46
	Champagne (22kt Gold)	27 803 892-47 0010
	Champagne (22kt Gold)	27 803 892-47
	Brushed Chrome	27 803 892-93
	Brushed Chrome	27 803 892-93 0010
	Brushed Dark Platinum	27 803 892-99
	Brushed Dark Platinum	27 803 892-99 0010

Recommended miscellaneous



Concealed wall elbow -

35 085 970 90

- max. recess depth 163 mm
- min. recess depth 90 mm

27 803 892 Product version from 6/30/2015 to 7/21/2020

mm [inches]



Flow rate chart



Codes & Standards

DIN 4109

EN 1717

ISO 3822

Ü-Zeichen



TARA Hand shower set with individual rosettes - Brushed Platinum

TARA

27 803 892 Product version from 6/30/2015 to 7/21/2020

Certificates and sustainability

Belgaqua_21-024-2 LGA_29



Spare parts list

No.	Item Number	Name	Quantity used	Delivery time
2	28 050 892-06	TARA Wall bracket - Brushed Platinum	1.00	10
1	28 450 892-06	connection	1.00	60
4	28 014 979-06	shower	1.00	60
3	28 104 970-06	Metal shower hose 1/2" x 1/2" x 1250 mm - Brushed Platinum	1.00	2